



CONVERSION  
SCALES




Feet	Meters
1	3048
2	6096
3	9144
4	12192
5	15240
6	18288
7	21336
8	24384
9	27432
10	30480

To convert feet to meters  
multiply by 0.3048  
To convert meters to feet  
multiply by 3.2808



Mapped by the Defense Mapping Agency and the National Ocean Service  
Published for civil use by the Geological Survey  
Topography by photogrammetric methods from aerial photographs taken 1951. Field checked 1951  
Bathymetry compiled by the National Ocean Service from tide-coordinated hydrographic surveys. This information is not intended for navigational purposes  
Mean low water (dotted) line and mean high water (heavy solid) line compiled by NOS from tide-coordinated aerial photographs. Apparent shoreline (outer edge of vegetation) shown by light solid line  
Polyconic projection. 1927 North American Datum  
10,000-foot grid based on Oregon coordinate system, north zone  
1000-meter Universal Transverse Mercator grid, zone 10  
To place on the predicted North American Datum 1983, move the projection lines 24 meters north and 97 meters east as shown by dashed corner ticks  
There may be private inholdings within the boundaries of the National or State reservations shown on this map  
Revisions shown in purple compiled by the Geological Survey from aerial photographs taken 1981 and other sources  
This information not field checked. Map edited 1984



HYDROGRAPHIC SURVEY INFORMATION			
SURVEY NUMBER	SURVEY DATE	SURVEY SCALE	SURVEY LINE SPACING (NAUT. MILES)
H-8417	1958	1:20,000	.03-.35
H-8421	1958	1:10,000	.01-.17
H-8423	1958	1:10,000	.02-.14

SCALE 1:24 000  
1 1000 0 1000 2000 3000 4000 5000 6000 7000 FEET  
1 5 10 15 20 KILOMETER

MAXIMUM ELEVATION LESS THAN 50 FEET  
DASHED LINES REPRESENT 25 FOOT CONTOURS  
NATIONAL GEODETIC VERTICAL DATUM OF 1929  
BATHYMETRIC CONTOUR INTERVAL 2 METERS WITH SUPPLEMENTARY 1 METER CONTOURS - DATUM IS MEAN LOWER LOW WATER  
THE RELATIONSHIP BETWEEN THE TWO DATUMS IS VARIABLE  
THE MEAN RANGE OF TIDE IS APPROXIMATELY 2.4 METERS

BASE MAP COMPLIES WITH NATIONAL MAP ACCURACY STANDARDS  
BATHYMETRIC SURVEY DATA COMPLIES WITH INTERNATIONAL HYDROGRAPHIC ORGANIZATION (IHO) SPECIAL PUBLICATION 44 ACCURACY STANDARDS AND/OR STANDARDS USED AT THE DATE OF THE SURVEY  
FOR SALE BY U. S. GEOLOGICAL SURVEY, DENVER, COLORADO 80225, OR RESTON, VIRGINIA 22092  
AND NATIONAL OCEAN SERVICE, ROCKVILLE, MARYLAND 20852  
A FOLDER DESCRIBING TOPOGRAPHIC MAPS AND SYMBOLS IS AVAILABLE ON REQUEST

ROAD CLASSIFICATION

- Primary highway, hard surface
- Light-duty road, hard or improved surface
- Secondary highway, hard surface
- Unimproved road
- Interstate Route
- U. S. Route
- State Route

CLATSOP SPIT, OREG.  
46124-B1-TB-024

1951  
PHOTOREVISED 1984  
BATHYMETRY ADDED 1984  
DMA 1178 11 NE - SERIES Y892

QUADRANGLE LOCATION

UTM GRID AND 1984 MAGNETIC NORTH DECLINATION AT CENTER OF SHEET